




















## Accessories

Model	TANTUM 15 Boiler	TANTUM 25 Boiler	TANTUM 35 Boiler	TANTUM 25 Combination	TANTUM 25 Compact 100	Order No.	Price/€
Measurement and reducing fitting DN80/125 x 60/100	X	X	X	X	X	1004271	159.00
 Boiler connection fitting, concentric, DN80/125, straight type	X	X	X	X	X	1000361	56.40
 Boiler connection fitting DN 60/100 87 ° bend	X	X	X	X	X	1002092	64.00
 Boiler connection fitting, concentric, DN80/125, 87° bend, H = 220 mm	X	X	X	X	X	1001918	91.00
 TANTUM connection set Consisting of two corrugated pipes 340 mm, two RD 3/4"-1/2" and four seals 3/4"	X	X	X	—	—	1000411	67.50
 TANTUM ball valve connection set, 3-way ball valve for simultaneous draining of the heater	X	X	X	X	—	1002526	117.87
 TANTUM ball valve connection set as straight pattern type + drinking water approval	X	X	X	X	—	1002528	148.65
 Storage tank sensor - for measuring the storage tank temperature	X	X	X	—	—	1001529	24.90
 TANTUM / INOX outdoor sensor	X	X	X	X	X	1003396	19.30
Required accessory options for time control of the heating system							
 T3M room thermostat, weekly program, Open Therm, with cable. Installation required in living space. Heating opera- tion is outside temperature compensat- ed and depends on the registered room temperature. Room temperature influ- ence can be switched on and off	X	X	X	X	X	1004269	145.00
 RSC-OT room unit	X	X	X	X	X	1001793	355.00

## Accessories

	Model	TANTUM 25 Heating	TANTUM 25 Combination	TANTUM 25 Compact 100	Order No.	Price/€
	CETA 104 Heating controller for single stage or modulating heating appliances (OpenTherm), direct heating circuit and hot water, incl. outdoor sensor and 2 boiler sensors	X	X	X	1001798	293.60
	CETA 106 Heating controller for mixer heating circuit differential temperature control, incl. outdoor sensor and flow sensor	X	X	X	1001799	272.00
	CETA 107 Heating controller for one-stage or modulating heating appliance OT-Bus, extension of mixed heating circuit and direct heating circuit, including flow sensor	X	X	X	1003456	550.00
	CETA RC EbV room remote control	X	X	X	1001756	164.80
	TANTUM hydraulic separator This hydraulic separator is matched to the TANTUM: Size DN 80/120, nominal size DN40, Connection sockets G 1 1/2", output 44 kW, Throughput 4 m³/h, max. allowable operating temperature +110°C, minimum allowable operating temperature -20°C, max. allowable operating pressure 6 bar	X	X	—	1002678	475.00
	Magnetite filter 3/4"	X	X	X	1002677	215.00
	Inhibitor inhibits boiler scale and all types of corrosion 0.5 litre bottle is sufficient for 100 litre of heating water	X	X	X	1002676	47.70
	Cleaner for heating systems for the commissioning of new systems or as sludge remover, 0.5 litre bottle is sufficient for 100 litre heating water	X	X	X	1002675	49.60
	Grundfos condensate removal pump	X	X	X	1000412	389.04